ITEM #VARIES

# P-HDU SERIES CRESCENT WASHERS

Crescent washers are used with holdown anchors to seat the anchor bolt or threaded rod at the correct angle and distribute load across the holdown seat. Their curved profile allows installation where offset placement or edge clearance is needed.

Manufactured from galvanized steel for exterior and exposed conditions, the washers are sized to match the Proponents P-HDU series: 3/4 in. for the P-HDU4 and 1 in. for the P-HDU14.





## SPECIFICATIONS

| | |
|---|---|
| **APPLICATIONS** | Designed for use in applications commonly served by holdown anchors.<br>• Shear wall framing assemblies<br>• Post-to-foundation anchorage<br>• Stud-to-foundation connections<br>• Wood-framed structural assemblies |
| **MATERIAL** | Zinc-Plated Steel |
| **FEATURES** | • Predeflected holdown configuration<br>• Compatible with anchor bolts or threaded rod installations<br>• Includes crescent washer for offset anchor placement<br>• SDS screws provided for wood member attachment<br>• Galvanized steel construction for corrosion resistance |
| **INSTALLATION NOTES** | Proponents hardware is engineered for dimensional compatibility with industry standard connector profiles. Products are manufactured to published industry specifications. Fastener type, quantity, and installation requirements should be verified by the installer or design professional based on project requirements and applicable building codes. |
| **WARRANTY** | Limited 1-Year |

| **AVAILABLE MODELS** | | | |
|---|---|---|---|
| **DESCRIPTION** | **CRESCENT WASHER HOLE SIZE** | **USE WITH** | **ITEM #** |
| Crescent Washer | 3/4" | P-HDU4 (H1629) | H1659 |
| Crescent Washer | 1" | P-HDU14 (H1628) | H1660 |