ITEM #VARIES

MORE STYLES AVAILABLE

SINGLE HUNG, DUAL GLAZED WINDOW

Energy-efficient vinyl single-hung window with dual-pane Low-E glass (.23 SHGC / .30 U-Factor) and a beige vinyl frame. A sealed double-pane window with argon gas between the panes to improve thermal performance and reduce energy loss. Certified by NFRC and AAMA for code-ready performance.



SPECIFICATIONS

APPLICATIONS	• Residential new construction and replacement window installations • Single-family homes and multifamily housing • Coastal or high-humidity environments • Warm-climate regions requiring energy-efficient glazing
MATERIAL	Vinyl frame with dual-glazed tempered Low-E glass (5 mm / 16 mm argon gas / 5 mm)
FEATURES	• Single-hung design with operable bottom sash and fixed top sash • Tilt-in bottom sash for easier interior cleaning • Dual-glazed Low-E insulated glass unit
INSTALLATION NOTES	Install the window into a properly sized rough opening, maintaining approximately 6 mm (1/4") of shim space on all sides. Secure the frame through each pre-drilled hole using 2" galvanized roofing nails, or longer if required to reach solid framing. Confirm the unit is level, plumb, and square before final fastening. Seal the exterior perimeter with 100% silicone for weather resistance. Installation must comply with all applicable local building codes and permit requirements.
PRODUCT RATING	Class R-PG50 951 x 2061 (37 x 81)-LWSHDX Design Pressure: ±2400 Pa (±50 psf) Water Penetration Resistance Test Pressure: 0 Pa (0.00 psf) NAMI approved and AAMA certified performance ratings
WARRANTY	Limited 10-Year

AVAILABLE FINISHES

White

Almond



QUICK SHIP OPTION

SIZE CODE	WIDTH	HEIGHT
2030	24"	36"
2040	24"	48"
2050	24"	60"
3030	36"	36"
3040	36"	48"
3050	36"	60"
4030	48"	36"
4040	48"	48"
4050	48"	60"