ITEM #VARIES

MORE STYLES AVAILABLE

EXTERIOR DOOR 2-PANEL STEEL

This 2-panel steel prehung door features 25GA steel skins with a fireproof board core and a UL 20-minute fire rating. Prehung on a finger-jointed wood frame with stainless steel hinges (including a spring self-closing top hinge), it includes an ADA-compliant PVC sill, fireproof weatherstripping, and double-bore lock prep.

Available in left- or right-hand inswing, the unit arrives fully aligned for quick installation and is impact-tested for added durability.





SPECIFICATIONS

APPLICATIONS	• Residential front or side entry doors • Multi-family housing units • Apartment entry doors • Light commercial fire-rated openings
MATERIAL	Galvanized steel door panel with fireproof core and finger-jointed wood jamb
FEATURES	• 20-minute UL fire-rated steel door • Prehung door with factory-installed frame • Adjustable threshold for installation flexibility • Double-bore lock preparation • Weatherstripping with ADA-compliant PVC sill
INSTALLATION NOTES	Ensure jamb and sill are level and square before fastening. Shim at hinge and lock locations for proper alignment. Apply sealant beneath the sill for weather resistance. Follow applicable UL installation guidelines to maintain fire rating.
DIMENSIONS	See below for options
WARRANTY	Limited 3-Year Warranty

WIDTH	HEIGHT	THICKNESS
32"	80"	1-3/8"
36"	80"	1-3/8"

QUICK SHIP OPTION